

Commissioning of EZ motors on Kollmorgen drive controllers Information

en-US
04/2023
ID 443236_en.01

1 Overview

This document contains information about the **Kollmorgen S300/400/600/700** feature that is offered in the configuration of STOBBER motors when selecting the drive controller type. This feature affects the connection and parameterization of STOBBER synchronous servo motors to drive controllers of the Kollmorgen S300/S400/S600/S700 series.

STOBBER motor designs with the previously named features are available and can be delivered.

STOBBER has taken the following measures to minimize the effort of commissioning STOBBER motors connected to Kollmorgen drive controllers and avoid errors during parameterization:

- The commutation offset of the motor was set so that calibration by the customer is not necessary.
- Parameter lists are provided on request.

2 Kollmorgen drive controllers

Supported series

This document refers to Kollmorgen drive controllers of the S300/S400/S600/S700 series. Of those, the S400 and S600 series from Kollmorgen have been discontinued.

Parameterization

Automatic parameterization of STOBBER motors to Kollmorgen drive controllers is not possible. STOBBER provides parameter lists in PDF format on request, however. More information can be found in the chapter Parameterizing the motor.

Connection cables

The plug connectors and terminal assignment of STOBBER motors are designed so that the customer can obtain and connect the corresponding original cables from Kollmorgen. STOBBER does not offer any connection cables for Kollmorgen drive controllers.

3 STOBBER motors

Supported motor series

The STOBBER EZ motor series can be parameterized to Kollmorgen drive controllers. Other STOBBER motor series on request.

Electronic nameplate

When connecting STOBBER motors to Kollmorgen drive controllers, the electronic nameplate is not used. Only the commutation offset is stored in the encoder memory so that it can be read out by the drive controller.

Temperature sensor

As standard, PTC or PT1000 temperature sensors are installed in Kollmorgen motors, depending on the series. STOBBER offers the same temperature sensors. The temperature sensor connections are routed via the encoder plug connector.

3.1 Encoders

Encoders with EnDat 2.2 interface

Encoder model	Code	Measuring method	Recordable revolutions	Resolution	Position values per revolution	MTTF [years]	PHF [h]
EnDat 2.2 EQI 1131	Q6	Inductive	4096	19 bit	524288	> 100	$\leq 15 \times 10^{-9}$
EnDat 2.2 EQI 1131 FMA	M4	Inductive	4096	19 bit	524288	> 100	$\leq 15 \times 10^{-9}$

Encoders with EnDat 2.1 interface

Encoder model	Code	Measuring method	Recordable revolutions	Resolution	Position values per revolution	Periods per revolution	MTTF [years]	PHF [h]
EnDat 2.1 EQN 1125 FMA	M2	Optical	4096	13 bit	8192	Sin/cos 512	> 57	$\leq 2 \times 10^{-6}$
EnDat 2.1 EQN 1125	Q4	Optical	4096	13 bit	8192	Sin/cos 512	> 57	$\leq 2 \times 10^{-6}$

Notes

- The encoder code is a part of the type designation of the motor.
- FMA = Version with fault exclusion for mechanical coupling.
- Multiple revolutions of the motor shaft can be recorded only using multi-turn encoders.

3.2 Possible combinations with drive controllers

The following table shows the possible combinations of STOBER synchronous servo motors with drive controllers from Kollmorgen depending on the encoder model.



Drive controller		Servostar S300/S400/S600/S700
Drive controller code		FE
Connection plan ID		442311
Encoder	Encoder code	
EnDat 2.2 EQI 1131	Q6	EZ
EnDat 2.2 EQI 1131 FMA	M4	EZ
EnDat 2.1 EQN 1125 FMA	M2	EZ
EnDat 2.1 EQN 1125	Q4	EZ
Resolver	R0	EZ

The encoder and drive controller codes are a part of the type designation of the motor.



3.3 Connection assignment of the power plug connector

The size and connection plan of the power plug connector depend on the size of the motor. The colors of the connecting wires inside the motor are specified in accordance with IEC 60757.

Plug connector size con.23

Connection diagram	Pin	Connection	Color
	1	U phase	BK
	3	W phase	RD
	4	V phase	BU
	A	Brake +	RD
	B	Brake -	BK
	C		
	D		
		Grounding conductor	GNYE


Plug connector size con.40 (1.5)

Connection diagram	Pin	Connection	Color
	U	U phase	BK
	V	V phase	BU
	W	W phase	RD
	+	Brake +	RD
	-	Brake -	BK
	1		
	2		
		Grounding conductor	GNYE


3.4 Connection assignment of the encoder plug connector

The size and connection assignment of the encoder plug connectors depend on the model of encoder installed and the size of the motor.

EnDat 2.1 encoder with sin/cos incremental signals, plug connector size con.23

Connection diagram	Pin	Connection	Color
	1	B - (Sin -)	RDBK
	2	0 V GND	WHGN
	3	A - (Cos -)	YEBK
	4	Up +	BNGN
	5	Data +	GY
	6		
	7	1TP1 (Temperature sensor +)	BK/RD
	8	Clock +	VT
	9	B + (Sin +)	BUBK
	10	0 V sense	WH
	11	A + (Cos +)	GNBK
	12	Up sense	BU
	13	Data -	PK
	14	1TP2 (Temperature sensor -)	WH/WH
	15	Clock -	YE
	16		
	17		

Resolver, plug connector size con.23

Connection diagram	Pin	Connection	Color
	1		
	2	1TP1 (Temperature sensor +)	BK/RD
	3	S4 Sin +	BU
	4	S3 Cos +	BK
	5	R2 Ref +	YEWB
	6	1TP2 (Temperature sensor -)	WH/WH
	7	S2 Sin -	YE
	8	S1 Cos -	RD
	9	R1 Ref -	RDWH
	10		
	11		
	12		

4 Parameterizing the motor

Prerequisites

Before parameterizing the motor, make sure that the following prerequisites are present or have been met:

- PC with Kollmorgen DriveGUI software
- Mechanical installation of the EZ motor in the machine is completed
- Electrical connection of the EZ motor to the Kollmorgen drive controller is complete

Parameterize the STOBBER motor using DriveGUI. The necessary parameter values can be obtained from STOBBER in list form.

The correct commutation offset is already stored in the motor encoder.

Further information on commissioning can be found in the technical documentation of the DriveGUI software, the drive controller and motor.

The technical documentation of a STOBBER motor can be found by entering the motor's serial number under <https://id.stober.com> or scanning the QR code on the motor's nameplate.



443236_en.01

04/2023

STÖBER Antriebstechnik GmbH + Co. KG
Kieselbronner Str. 12
75177 Pforzheim
Germany
Tel. +49 7231 582-0
mail@stoeber.de
www.stober.com

24 h Service Hotline
+49 7231 582-3000

www.stober.com